



LIGHTWEIGHT CONCRETE TECHNOLOGY AND APPLICATION

SIKA EGYPT

ENG. ASHRAF ELZINY

Technical & Export Manager

BUILDING TRUST




AREA OF APPLICATION

As a lightweight, low-viscous filling material for:

- Building as thermal insulating layer
(Measuring indicative thermal conductivity test in **BS 874 part 3.2**)
- Shutdown sewerage.
- Fill blocks, spaces around pipes,etc.

LIGHTWEIGHT CONCRETE TECHNOLOGY AND APPLICATION

Cellular Concrete System




LIGHTWEIGHT CONCRETE TECHNOLOGY AND APPLICATION

Lighter than water!



LIGHTWEIGHT CONCRETE TECHNOLOGY AND APPLICATION

Composition of Cellular Concrete




LIGHTWEIGHT CONCRETE TECHNOLOGY AND APPLICATION

Cellular Concrete - Properties

Fresh Concrete	Hardened Concrete
<ul style="list-style-type: none">■ flowable■ pumpable■ easy workability■ no compaction necessary	<ul style="list-style-type: none">■ Adjustable in unit weight and strength■ durable and stable in shape■ Thermal insulating■ higher resistance to fire■ increased shrinkage■ not decomposable

LIGHTWEIGHT CONCRETE TECHNOLOGY AND APPLICATION

Compressive Strength of Cellular Concrete Depending on Dry Unit Weight



LIGHTWEIGHT CONCRETE

TECHNOLOGY AND APPLICATION

Components of Cellular Concrete

Type	Usual Materials
cement	CEM I 32,5 R CEM I 42,5 R
filler	limestone flour fly ash
aggregates	sand 0 – 2 mm 0 – 4 mm
foam agent	SB 2 - Organic tenside
stabilizer	ST 3 - powder, (methyl cellulose)

LIGHTWEIGHT CONCRETE TECHNOLOGY AND APPLICATION

Mix Design of Cellular Concrete

Cement content	300 - 350 kg/m³
Water content	150 l/m³ with foam generator SG 70 180 l/m³ with foam generator SG S 9
Foam unit weight	0,03 – 0,06 kg/l with foam generator SG 70 0,03 – 0,05 kg/l with foam generator SG S 9

LIGHTWEIGHT CONCRETE TECHNOLOGY AND APPLICATION


Production on the Site

Concrete mixing plant

sand
cement water



(compulsory mixer)




On the site with foam generator SG 70

foam agent
SB 2

water



Foam production with foam
generator SG 70



FOAM AGENT SB2


FOAM AGENT FOR THE PRODUCTION OF POROUS LIGHTWEIGHT CONCRETE BY FOAMING METHOD

Technical Data

Colour and state :	blue-green liquid
Density (20°C):	1.04 g/cm ³
Chloride content:	< 0.1 %
Recommended dosage:	150 – 230 g / 100 l foam

LIGHTWEIGHT CONCRETE TECHNOLOGY AND APPLICATION

Foam Generator SG 70




LIGHTWEIGHT CONCRETE TECHNOLOGY AND APPLICATION

Foam production with SGS 9



LIGHTWEIGHT CONCRETE TECHNOLOGY AND APPLICATION


Applications: Re-Filling of Trenches and Excavations



- filling of working spaces at the side of pipes
- avoiding consolidation settlement

LIGHTWEIGHT CONCRETE TECHNOLOGY AND APPLICATION

Applications: Filling of Sewage Pipes



- Pouring directly in the shaft
- Complete filling of the cross-section

LIGHTWEIGHT CONCRETE TECHNOLOGY AND APPLICATION

Applications: Cellular Concrete below Basement Slab



LIGHTWEIGHT CONCRETE TECHNOLOGY AND APPLICATION

Applications: Filling between Floor Timbers



LIGHTWEIGHT CONCRETE TECHNOLOGY AND APPLICATION

Applications: Roof Surface with Cellular Concrete as levelling layer

