

## Safety Data Sheet

## **TRADE NAME :** SIKA Ferrogard 903

May 2018

Page 1/4

1.1	Chemical One component based on organic compounds.		
1.2	<b>Characterization :</b> <b>Form:</b> Liquid	Color: Transparent	Odor: None.
2.	Physical Data and Safety DataDensity20° CpH :Flash PointHazardous decomposition prod	~ 1.04 Kg/l ~ 10 > 212 ° F ucts None known.	
	Hazardous Reactions	Exothermic reaction	
3.	<b>Safety Precautions</b> Avoid contact with skin and eyes.		
4.	Protective measures storage and handling		
4.1	<b>Technical protective measures</b> Storage temperature between + 5 : + 30 °C Keep container tightly closed. Keep away from heat and frost. Keep away from extremes of cold.		
4.2	Personal Protective Equipment Respiratory protection: Eye Protection : Hand Protection: Others :	Protection mask. Tightly fitting protective Gloves. E.g. rubber , min	goggles nimum thickness 1.4 mm right protective clothing
4.3	<b>Industrial Hygiene</b> During use. Eating, drinking or smoking is not allowed. Remove immediately contaminated clothing. Wash hands before breaks and after work.		
4.4	<b>Protection Against Fire and Explosion</b> In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-		

contained breathing apparatus with a full face piece operated in the pressure demand or other positive pressure mode

## 4.5 Disposal

Dispose as special waste: mixture of water and hydrocarbons.

- 5. Measures in Case of Accidents Fight fire with CO<sub>2</sub>, Foam or dry powder.
- **5.1** After spillage or leakage Remove with absorbing material and dispose as prescribed Remove residues with water.

# **5.2 Extinguish media:** Water, foam carbon dioxide, dry powder.

N.A = not applicable

blank = no data available



## TRADE NAME : SIKA Ferrogard 903

#### 5.3 First Aid:

In case of contact with eyes. Rinse immediately under running water for 15 minutes with eyelids open. Seek medical advice.

Take off immediately all contaminated clothing. Wash contaminated skin with plenty of soap and water.

If swallowed, drink copious amounts of water without delay and seek medical advice. Do not induce vomiting.

### 6. Transport

Non-hazardous.

#### 7. Toxicology

Non-toxic under relevant health and safety codes.

#### 8. Ecology

Don't release into water supplies or the ground. In cured state the product is not known to cause an adverse environmental effect. Because of the high pH value the product can be injurious to aquatic life.

#### 9. Stability and reactivity

Chemical stability

This material is thermally stable when stored and used as directed.

Conditions to avoid: Evaluated temperatures.

Incompatible Materials: No information available.

Hazardous decomposition products: Oxides of carbon, smoke and other toxic fumes.

Hazardous reactions: No information available.

#### **10.** Disposal considerations

Refer to State/Territory Land Waste Management Authority.



## **TRADE NAME :** SIKA Ferrogard 903

**11. Regulatory information** Poisons Schedule (Aust): Not applicable.

12. Handling and storage Handling : Avoid skin and eye contact.

#### **Storage:**

Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in section 9. Keep containers closed when not in use – check regularly for leaks.

#### 13. Exposure controls/personal protection

National occupational exposure limits: No value assigned for this specific material

#### **Biological limit values:**

As per the "National Model Regulations for the control of Workplace Hazardous Substances [NOHSC: 1005 (1994)]" the ingredients in this material do not have a Biological Limit Allocated.

#### **Engineering measures:**

Provide exhaust ventilation where operating conditions may create excessive work place vapor or mists.

#### **Personal protection equipment:**

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.

Wear overalls, safety glasses and impervious gloves.

#### 14. Fire-fighting measures:

Specific hazards: Non – combustible material.

Specific protective precautions and equipment: Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapor or products of combustion.



## **TRADE NAME :** SIKA Ferrogard 903

Page 4/4

- **15.** Hazard identification Hazard Category: Risk Phrase(s) : Safety Phrase(s):
- 16. Consumption/information on ingredients Chemical characterization: Thixotropic epoxy resin.

Hazardous ingredients:

**SIKA EGYPT** Cairo Sales Office 222 El Hegaz St. , Heliopolis P.O. Box : 2943 El Horria (11361) Cairo Phone : +202 - 26235032 / 4 Fax : +202 - 26235637 Alex. Sales & Factory 4, Mohamed Masoud St. ,Beh. Olemby Club P.O.Box 2579 El Sarai + Alexandria Phone : 4244601 /2/3/5 Fax : 4244604 Borg El Arab Factory Tel. : 4592654 - 4591417 Fax: 4592036