

# TRADE NAME : SIKA Top Seal 107 (A)

Chemical 1.1 Acrylic Aquous emulsion 1.2 Characterization : Odor: Characteristic. Form: Liquid **Color**: Milky-White 2. Physical Data and Safety Data Density @ 20° C ~ 1.01 ± 0.02 Kg/l **pH Value** (100 g/l  $H_2O$ ) 7.5 (typical) Flash Point >200° F Melting Point 32° F 0° C Boiling Point 212° F 100° C Hazardous decomposition products After evaporation of water, combustion will generate: oxides of carbon. Acrylic monomers, acrid smoke and irritating fumes. **Hazardous Reactions** Exothermic reaction. 3. Regulation. A void contact with skin and eyes. 4. Protective measures storage and handling 4.1 Technical protective measures Storage temperature min/max. : +5 / +25° C Keep only in the original container. Keep container tightly closed. Keep away from heat and frost. Avoid dust formation during mixing application. Keep away from extremes of cold. 4.2 **Personal Protective Equipment** Respire. : Protection mask. Eve Protection : Tightly fitting protective goggles Hand Protection: Gloves. E.g. rubber, minimum thickness 1.4 mm Others : N.A 4.3 **Industrial Hygiene** During use. Eating, drinking or smoking is not allowed. Remove immediately contaminated clothing. Wash hands before breaks and sifter work. **Protection Against Fire and Explosion** 4.4 N.A.

#### 4.5 Disposal

Arrange for disposal via a licensed waste contractor. Dispose of containers with care. Empty packaging should be removed by a licensed waste contractor.

Dispose as special waste: mixture of water and hydrocarbons.

Feb. 2008

Page 1/2

# TRADE NAME : SIKA Top Seal 107(A)

Sweep up with sweeping aid and dispose as prescribed Remove residues with water.

**Extinguish media:** Water. Foam carbon dioxide, dry powder. **Not to be used** : N.A.

# First Aid:

In case of contact with eyes. Rinse immediately under running water for 15 minutes with eyelids open. Seek medical advice.

Take off immediately all contaminated clothing. Wash contaminated skin with plenty of soap and water.

If swallowed, drink copious amounts of water without delay and seek medical advice. Do not induce vomiting.

# 7. Transport

Non-hazardous. Not regulated per D.O.T.

## 8. Safety Precautions

Contact with eyes, skin and mucous membrane causes burns. Sensitization and allergic reactions may occur due to its cement base.

# 9. Toxicology

Non-Toxic under relevant health and safety codes.

## 10. Ecology

Don't dispose of into water or soil, but according to local regulations. In cured state the product is not known to cause an adverse environmental effect. Because of the effect of pH value the product can be injurious to aquatic life.

# SIKA EGYPT

**Cairo Sales Office** El Obour City – 1<sup>st</sup> Industrial Zone Block no. 13035/10 P.O. Box : 2943 El Horria (11361) Cairo Phone : +2-02-46100715/ 8 Fax : +2-02-46100759





Alex. Sales Office 4, Mohamed Masoud St. ,Beh. Olemby Club P.O.Box 2579 El Sarai + Alexandria Phone : 4244601 /2/3/5 Fax : 4244604 Borg El Arab Factory Tel. : 4592654 - 4591417 Fax: 4592036



#### Feb 2008 TRADE NAME : SIKA Top Seal 107(B) Page 1/2 1.1 Chemical Mixture of cement, additive and sand ready for use as a waterproofing. 1.2 Characterization : Form : powder **Color** : gray Odor : none 2. **Physical Data and Safety Data** Density 20° C ~ 1.9 Kg/l **pH Value** $(100 \text{ g/l H}_2\text{O})$ 14 Flash Point > 200° F N/AV ° F Melting Point Boiling Point N/AV ° F Thermal decomposition 550 Degrees Celsius Hazardous decomposition products Cao **Hazardous Reactions** Exothermic reaction with acids. 3. Regulation. A void contact with skin and eyes. 4. Protective measures storage and handling 4.1 **Technical protective measures** Storage temperature min/max. : +5 / +40° C Keep only in the original container. Keep container tightly closed. Keep away from heat and frost. Avoid dust formation during application. Keep away from acids. 4.2 ' Personal Protective Equipment Respire. : Dust protection mask. Eve Protection : Tightly fitting protective goggles Gloves. E.g. rubber, minimum thickness 1.4 mm Hand Protection: Others : N.A 4.3 Industrial Hygiene During use. Eating, drinking or smoking is not allowed. Remove immediately contaminated clothing. Wash hands before breaks and safter work. 4.4 **Protection Against Fire and Explosion** N.A. 4.5 Disposal Dispose as special waste: mixture of water and hydrocarbons. Measures in Case of Accidents and Fires 5. 5.1 After spillage or leakage Sweep up with sweeping aid and dispose as prescribed Remove residues with water. 5.2 Extinguish media: Water. Foam carbon dioxide, dry powder. Not to be used : N.A.

# TRADE NAME : SIKA Top Seal 107(B)

# 5.3 First Aid:

In case of contact with eyes. Rinse immediately under running water for 15 minutes with eyelids open. Seek medical advice.

Take off immediately all contaminated clothing. Wash contaminated skin with plenty of soap and water.

If swallowed, drink copious amounts of water without delay and seek medical advice. Do not induce vomiting.

## 6. Transport

Non-hazardous. Not regulated per D.O.T.

## 7. Safety Precautions

Contact with eyes, skin and mucous membrane causes burns. Sensitization and allergic reactions may occur due to its cement base.

#### 8. Toxicology

Non-Toxic under relevant health and safety codes.

# 9. Ecology

Don't dispose of into water or soil, but according to local regulations. In cured state the product is not known to cause an adverse environmental effect. Because of the high pH value the product can be injurious to aquatic life.

**SIKA EGYPT** Cairo Sales Office El Obour City – 1<sup>st</sup> Industrial Zone

Block no. 13035/10 P.O. Box : 2943 El Horria (11361) Cairo Phone : +2-02-46100715/8 Fax : +2-02-46100759





Alex. Sales Office 4, Mohamed Masoud St. ,Beh. Olemby Club P.O.Box 2579 El Sarai + Alexandria Phone : 4244601 /2/3/5

Fax : 4244604 Borg El Arab Factory Tel. : 4592654 - 4591417 Fax: 4592036

Page 2/2