



Sikadur-41 CF Normal/Rapid/Slow Part A

Date of issue - 31/03/2006.

SKD41CFA

1. PRODUCT AND COMPANY IDENTIFICATION

Product Code	SKD41CFA
Product Name	Sikadur-41 CF Normal/Rapid/Slow Part A
Product Description	3-Component epoxy resin based patching and repair mortar.
Manufacturer/Supplier	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129

2. COMPOSITION/INFORMATION ON THE COMPONENTS**Preparation - Hazardous ingredients (Europe)**

Component	CAS/EINECS	Concentration	Classification	Risk Phrases
Reaction product: bisphenol-A (epichlorohydrin), epoxy resin(No Av. Mol.wt <= 700)	25085-99-8	10.00% - 25.00%	Xi, N	R36/38, R43, R51/53
Aliphatic glycidyl ether	68609-97-2	1.00% - 2.50%	Xi, N	R36/38, R43, R51/53
Solvent Naptha (petroleum) heavy aromatic.	64742-94-5	1.00% - 2.50%	Xn, N	R51/53, R65, R66 R67

3. HAZARD IDENTIFICATION

Main Hazards	Irritating to eyes and skin. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
---------------------	---

4. FIRST AID MEASURES

Eye Contact	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention urgently.
Skin Contact	Wipe off as much as possible with a clean dry cloth. Wash skin thoroughly with soap and water. If material proves difficult to remove, use suitable skin cleanser (not solvent). Solvents should not be used to clean skin because they may increase the penetration of the material.
Ingestion	Wash out mouth with water. Obtain medical attention.
Inhalation	Remove from exposure. In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure, obtain medical attention.

5. FIRE FIGHTING MEASURES

Extinguishing Media	Not readily combustible. Use foam, dry chemical or carbon dioxide.
Extinguishing Media - Not suitable	Do not use water jet.
Special Hazards of Product	Combustion will produce smoke, carbon dioxide and carbon monoxide.
Protective Equipment for Fire-Fighting	Wear full protective clothing and self-contained breathing apparatus.

**6. ACCIDENTAL RELEASE MEASURES**

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Prevent the material from entering drains or water courses.
<i>Spillages</i>	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

7. HANDLING AND STORAGE

<i>Handling</i>	Use in well ventilated area.
<i>Storage</i>	Storage area should be: cool. dry. Storage temperature should be controlled to between 5 and 25 °C. Store in the original container securely closed . Keep away from foodstuffs

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
<i>Respiratory Protection</i>	Respiratory protection not normally required.
<i>Hand Protection</i>	Wear suitable impervious gloves. (butyl / nitrile type) The insides of gloves must be kept scrupulously clean.
<i>Eye Protection</i>	Chemical goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES

<i>Physical State</i>	Paste.
<i>Color</i>	Light grey.
<i>Odor</i>	Characteristic.
<i>Flash Point °C</i>	Approx. 166
<i>Solubility - Water</i>	Insoluble.
<i>Density (kg/m³)</i>	Approx. 1940 at 20 °C.
<i>Viscosity (at 20°C)</i>	Thixotropic paste

10. STABILITY AND REACTIVITY

<i>Stability</i>	Stable under normal conditions.
<i>Hazardous Decomposition Products</i>	Heating may produce: oxides of carbon. acrid smoke and irritating fumes.

11. TOXICOLOGICAL INFORMATION

<i>Acute toxicity</i>	Low order of acute toxicity.
<i>Eye irritation</i>	Irritating to the eyes.
<i>Skin irritation</i>	Frequent or prolonged skin contact may cause some local short term skin irritation.
<i>Sensitization - Skin</i>	The low molecular weight epoxy resin is a potential skin sensitizer. The possibility of allergic sensitisation should be considered



SAFETY DATA SHEET

Sikadur-41 CF Normal/Rapid/Slow Part A

Date of issue - 31/03/2006.

SKD41CFA

12. ECOLOGICAL INFORMATION

<i>Mobility</i>	The product is insoluble in water.
<i>Persistence/degradability</i>	The product is expected to be not readily biodegradable.
<i>Ecotoxicity</i>	This material is harmful to aquatic organisms.


13. DISPOSAL

<i>Product Disposal</i>	Hazardous waste. Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

14. TRANSPORT INFORMATION

<i>ADR/RID : Proper shipping name</i>	Not Regulated under ADR/RID
<i>IMDG : Proper shipping name</i>	Not Regulated under IMDG
<i>IATA : Proper shipping name</i>	Not Regulated under ICAO

15. REGULATORY INFORMATION

<i>Label Requirements</i>	Irritant 
<i>Risk Phrases</i>	Irritating to eyes and skin. May cause sensitisation by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<i>Safety Phrases</i>	Avoid contact with skin. Wear suitable gloves. Contains epoxy constituents. See information supplied by the manufacturer.
<i>Contains</i>	reaction product: bisphenol A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700) oxirane, mono[(C12-14-alkyloxy)methyl]derivs.

16. OTHER INFORMATION

<i>First Issue Date</i>	31.3.2006
<i>Revisions Highlighted</i>	Future revisions will incorporate such information as is required but which is not available at this time.
<i>Uses and Restrictions</i>	Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.



SAFETY DATA SHEET

Sikadur-41 CF Normal/Rapid/Slow Part A

Date of issue - 31/03/2006.

SKD41CFA

UK Legislation

Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.

SI 20021689 Chemicals (Hazard Information and Packaging) Regulations

SI 2002/2677: The Control of Substances Hazardous to Health Regulations

SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.

SI 2005/ 894 Hazardous waste regulations 2005

General Approved Code of Practice to COSHH Regulations, HSE.

UK Guidance Publications

Footnote

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.

**1. PRODUCT AND COMPANY IDENTIFICATION**

Product Code SKDCFNB
Product Name Sikadur 31/41 CF Normal Part B
Product Description Epoxy resin hardener component
Manufacturer/Supplier Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire.
AL7 1BQ
tel. 01707 394444
Fax. 01707 329129

2. COMPOSITION/INFORMATION ON THE COMPONENTS**Preparation - Hazardous ingredients (Europe)**

Component	CAS/EINECS	Concentration	Classification	Risk Phrases
Benzyl Alcohol	100-51-6	2.50% - 10.00%	Xn	R20/22
Triethylenetetramine	112-24-3	2.50% - 10.00%	C	R21, R34, R43, R52/53
Solvent Naptha (petroleum) heavy aromatic.	64742-94-5	2.50% - 10.00%	Xn, N	R51/53, R65, R66 R67
2,4,6-Tri(dimethylaminomethyl) phenol	90-72-2	1.00% - 2.50%	Xn	R22, R36/38
Naphthalene, pure	91-20-3	0.10% - 1.00%	Xn, N	R22, R50/53, R40

3. HAZARD IDENTIFICATION

Main Hazards Irritating to eyes and skin.
May cause sensitization by skin contact.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

4. FIRST AID MEASURES

Eye Contact Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Eyelids should be held away from the eyeball to ensure thorough rinsing.
Obtain medical attention urgently.

Skin Contact Wipe off as much as possible with a clean dry cloth. Wash skin thoroughly with soap and water.
If material proves difficult to remove, use suitable skin cleanser (not solvent).
Solvents should not be used to clean skin because they may increase the penetration of the material.
Contaminated clothing should be washed or dry-cleaned before re-use.

Ingestion Do not induce vomiting.
Obtain medical attention.

Inhalation Remove from exposure. In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure, obtain medical attention.



SAFETY DATA SHEET

Sikadur 31/41 CF Normal Part B

Date of issue - 31/03/2006.

SKDCFNB

5. FIRE FIGHTING MEASURES

<i>Extinguishing Media</i>	Not readily combustible. Use foam, dry chemical or carbon dioxide.
<i>Extinguishing Media - Not suitable</i>	Do not use water jet.
<i>Special Hazards of Product</i>	Combustion will generate oxides of carbon and nitrogen
<i>Protective Equipment for Fire-Fighting</i>	Wear full protective clothing and self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Prevent the material from entering drains or water courses.
<i>Spillages</i>	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

7. HANDLING AND STORAGE

<i>Handling</i>	Exposure by inhalation or skin contact should be minimised by good Industrial Hygiene practices. Avoid contact with eyes, skin and clothing. Mix in a well ventilated area.
<i>Storage</i>	Storage area should be: cool. dry. Storage temperature should be controlled to between 5 and 25 °C. Store in the original container securely closed . Keep away from foodstuffs

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
<i>Respiratory Protection</i>	Respiratory protection not normally required.
<i>Hand Protection</i>	Wear suitable impervious gloves. (butyl / nitrile type) The insides of gloves must be kept scrupulously clean.
<i>Eye Protection</i>	Chemical goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES

<i>Physical State</i>	Paste.
<i>Color</i>	Dark Grey.
<i>Odor</i>	Amine like.
<i>pH</i>	Approx. 11 at 10% w/w in water.
<i>Flash Point °C</i>	Exceeds 100.
<i>Solubility - Water</i>	Partially soluble.
<i>Density (kg/m³)</i>	Approx. 1940 at 20 °C.
<i>Viscosity (at 20°C)</i>	Thixotropic paste



SAFETY DATA SHEET

Sikadur 31/41 CF Normal Part B

Date of issue - 31/03/2006.

SKDCFNB

10. STABILITY AND REACTIVITY

<i>Stability</i>	Stable under normal conditions.
<i>Hazardous Decomposition Products</i>	Heating may produce: ammonia. oxides of carbon. oxides of nitrogen. acrid smoke and irritating fumes.

11. TOXICOLOGICAL INFORMATION

<i>Acute toxicity</i>	Low order of acute toxicity.
<i>Eye irritation</i>	Irritating to the eyes.
<i>Skin irritation</i>	Frequent or prolonged skin contact may cause some local short term skin irritation.
<i>Sensitization - Skin</i>	May cause sensitisation. May cause allergic reactions to certain individuals.

12. ECOLOGICAL INFORMATION

<i>Mobility</i>	The product is sparingly soluble in water.
<i>Persistence/degradability</i>	The product is expected to be not readily biodegradable.
<i>Ecotoxicity</i>	This material is harmful to aquatic organisms.


13. DISPOSAL

<i>Product Disposal</i>	Hazardous waste. Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

14. TRANSPORT INFORMATION

<i>ADR/RID : Proper shipping name</i>	Not Regulated under ADR/RID
<i>IMDG : Proper shipping name</i>	Not Regulated under IMDG
<i>IATA : Proper shipping name</i>	Not Regulated under ICAO

15. REGULATORY INFORMATION

<i>Label Requirements</i>	Irritant 
<i>Risk Phrases</i>	Irritating to eyes and skin. May cause sensitization by skin contact. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<i>Safety Phrases</i>	Avoid contact with skin. Wear suitable gloves.
<i>Contains</i>	3-aminomethyl-3,5,5-trimethylcyclohexylamine 3,6-diazaoctanethylenediamine



SAFETY DATA SHEET
Sikadur 31/41 CF Normal Part B

Date of issue - 31/03/2006.

SKDCFNB

16. OTHER INFORMATION

<i>First Issue Date</i>	31.3.2006
<i>Revisions Highlighted</i>	Future revisions will incorporate such information as is required but which is not available at this time.
<i>Uses and Restrictions</i>	Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.
<i>UK Legislation</i>	Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions. SI 2002/1689 Chemicals (Hazard Information and Packaging) Regulations SI 2002/2677: The Control of Substances Hazardous to Health Regulations SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.
<i>UK Guidance Publications</i>	SI 2005/ 894 Hazardous waste regulations 2005 Approved Code of Practice - Management of Health and Safety at Work, HSE. General Approved Code of Practice to COSHH Regulations, HSE.
<i>Footnote</i>	The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.