



MATERIAL SAFETY DATA SHEET

Sikagard 62 - Part A (ALL COLORS)

HMIS

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	C

1. Product And Company Identification

Supplier

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Manufacturer

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Manufacturer Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Issue Date: 01/24/2006

Product Name: Sikagard 62 - Part A (ALL COLORS)

CAS Number: Not Established

Chemical Family: Epoxy Compound

MSDS Number: 3838

Product Code: 0601130

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
AROMATIC HYDROCARBON BLEND	68477-31-6	
EPOXY RESIN	25085-99-8	

3. Hazards Identification

Eye Hazards

EYE IRRITANT.

Skin Hazards

MAY CAUSE SKIN IRRITATION. PROLONGED AND/OR REPEATED CONTACT WITH SKIN MAY CAUSE AN ALLERGIC REACTION/SENSITIZATION.

Ingestion Hazards

ACUTELY TOXIC. HARMFUL IF ASPIRATED INTO LUNGS.

MATERIAL SAFETY DATA SHEET

Sikagard 62 - Part A (ALL COLORS)

3. Hazards Identification - Continued

Inhalation Hazards

MAY CAUSE RESPIRATORY TRACT IRRITATION.

4. First Aid Measures

Eye

RINSE EYES THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES. CONSULT PHYSICIAN.

Skin

WASH SKIN THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. IF SYMPTOMS PERSIST CONSULT PHYSICIAN.

Ingestion

DILUTE WITH WATER. DO NOT INDUCE VOMITING. CONTACT PHYSICIAN.

Inhalation

REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, INSTITUTE ARTIFICIAL RESPIRATION. CONSULT WITH PHYSICIAN.

5. Fire Fighting Measures

Flash Point: 355 °F

Autoignition Point: N/AV °F

Fire And Explosion Hazards

NONE KNOWN

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

WEARING PROPER PROTECTIVE CLOTHING, CONTAIN SPILL AND COLLECT WITH ABSORBENT MATERIAL. SHOVEL INTO CLOSABLE CONTAINERS. AVOID CONTACT.

7. Handling And Storage

Handling And Storage Precautions

STORE IN A COOL AREA. KEEP CONTAINERS TIGHTLY CLOSED.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

Eye/Face Protection

Safety glasses with side shields or goggles.

Skin Protection

AVOID SKIN CONTACT. WEAR LONG SLEEVE SHIRT AND LONG PANTS.
WEAR CHEMICAL RESISTANT GLOVES.

MATERIAL SAFETY DATA SHEET

Sikagard 62 - Part A (ALL COLORS)

8. Exposure Controls/Personal Protection - Continued

Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use.

Other/General Protection

WASH THOROUGHLY AFTER HANDLING.

Ingredient(s) - Exposure Limits

AROMATIC HYDROCARBON BLEND

ACGIH TLV: NOT ESTABLISHED

OSHA PEL: NOT ESTABLISHED

NTP: NO

IARC: NO

EPOXY RESIN

ACGIH TLV: NOT ESTABLISHED

OSHA PEL: NOT ESTABLISHED

NTP: NO

IARC: NO

9. Physical And Chemical Properties

Appearance

LIGHT YELLOW LIQUID

Odor

MILD AROMATIC ODOR

Chemical Type: Mixture

Physical State: Liquid

Melting Point: N/AV °F

Boiling Point: N/AV °F

Specific Gravity: 1.14

Percent Volatiles: 0%

Vapor Pressure: N/AV

Vapor Density: > AIR

Solubility: N/AV

Evaporation Rate: SLOWER THAN ETHER

10. Stability And Reactivity

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR

Conditions To Avoid (Stability)

NONE KNOWN

Incompatible Materials

STRONG OXIDIZING MATERIALS, ACIDS AND BASES.

Hazardous Decomposition Products

CO, CO₂, ALDEHYDES AND OTHER ORGANICS

Conditions To Avoid (Polymerization)

FIRES/EXOTHERM WHEN CURING IN MASS.

MATERIAL SAFETY DATA SHEET

Sikagard 62 - Part A (ALL COLORS)

11. Toxicological Information

Conditions Aggravated By Exposure

EYE DISEASE, SKIN DISORDERS AND ALLERGIES, CHRONIC RESPIRATORY DISEASE

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

Proper Shipping Name

NOT REGULATED UNDER D.O.T.

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard
Chronic Health Hazard

SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

16. Other Information

HMIS Rating

Health: 2

Fire: 1

Reactivity: 0

PPE: C

Revision/Preparer Information

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201-933-8800

This MSDS Supercedes A Previous MSDS Dated: 11/27/2001

Disclaimer

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A

M A T E R I A L S A F E T Y D A T A S H E E T

Sikagard 62 - Part A (ALL COLORS)

Disclaimer - Continued

MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800.

SIKA CORPORATION

Printed Using MSDS Generator™ 2000



MATERIAL SAFETY DATA SHEET

Sikagard 62 - Part B (ALL COLORS)

HMIS

HEALTH	3
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	C

1. Product And Company Identification

Supplier

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Manufacturer

Sika Corporation
201 Polito Ave
Lyndhurst, NJ 07071

Company Contact: EHS Department
Telephone Number: 201-933-8800
FAX Number: 201-933-9379
Web Site: www.sikausa.com

Supplier Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

Manufacturer Emergency Contacts & Phone Number

CHEMTREC: 800-424-9300
INTERNATIONAL: 703-527-3887

DOT NON CORROSIVE AS PER 11/3/97 TESTING

Issue Date: 01/24/2006

Product Name: Sikagard 62 - Part B (ALL COLORS)

CAS Number: Not Established

Chemical Family: Amine

MSDS Number: 3839

Product Code: 0601792

2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
AROMATIC HYDROCARBON BLEND	68477-31-6	
BENZYL ALCOHOL	100-51-6	
PROPRIETARY BLEND OF ALIPHATIC & CYCLIC AMINES	Not Establis	
SILICA, QUARTZ	14808-60-7	

*EXPOSURE TO SILICA, QUARTZ IS APPLICABLE ONLY IF CURED WITH PART "A" AND SANDED.

3. Hazards Identification

Eye Hazards

CONTACT MAY CAUSE SEVERE IRRITATION AND PAIN AND MAY CAUSE BURNS, NECROSIS AND PERMANENT INJURY. MAY CAUSE VISUAL DISTURBANCES, CORNEA DAMAGE, DAMAGE TO THE OPTIC NERVE OR BLINDNESS.

MATERIAL SAFETY DATA SHEET

Sikagard 62 - Part B (ALL COLORS)

3. Hazards Identification - Continued

Skin Hazards

CONTACT MAY CAUSE SEVERE IRRITATION AND PAIN AND MAY CAUSE BURNS, NECROSIS AND PERMANENT INJURY. PROLONGED AND/OR REPEATED CONTACT WITH SKIN MAY CAUSE AN ALLERGIC REACTION/SENSITIZATION.

Ingestion Hazards

ACUTELY TOXIC. HARMFUL IF ASPIRATED INTO LUNGS.

Inhalation Hazards

MAY CAUSE RESPIRATORY TRACT IRRITATION. OVEREXPOSURE MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS.

4. First Aid Measures

Eye

RINSE EYES THOROUGHLY WITH WATER FOR AT LEAST 15 MINUTES. CONSULT PHYSICIAN.

Skin

WASH SKIN THOROUGHLY WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. IF SYMPTOMS PERSIST CONSULT PHYSICIAN.

Ingestion

DILUTE WITH WATER. DO NOT INDUCE VOMITING. CONTACT PHYSICIAN.

Inhalation

REMOVE TO FRESH AIR. IF BREATHING HAS STOPPED, INSTITUTE ARTIFICIAL RESPIRATION. CONSULT WITH PHYSICIAN.

5. Fire Fighting Measures

Flash Point: >220 °F

Autoignition Point: N/AV °F

Fire And Explosion Hazards

EXPOSURE TO HEAT BUILDS UP PRESSURE IN CLOSED CONTAINERS.

Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO₂.

Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

6. Accidental Release Measures

WEAR SUITABLE PROTECTIVE EQUIPMENT. VENTILATE AREA. CONTAIN SPILL AND COLLECT WITH ABSORBENT MATERIAL AND TRANSFER INTO SUITABLE CONTAINERS. AVOID CONTACT.

7. Handling And Storage

Handling And Storage Precautions

STORE IN A COOL, DRY, WELL VENTILATED AREA. KEEP CONTAINERS TIGHTLY CLOSED.

Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

MATERIAL SAFETY DATA SHEET

Sikagard 62 - Part B (ALL COLORS)

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation.

Eye/Face Protection

Safety glasses with side shields or goggles.

Skin Protection

AVOID SKIN CONTACT. WEAR LONG SLEEVE SHIRT AND LONG PANTS. CHEMICAL RESISTANT GLOVES.

Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use. In areas where the Permissible Exposure Limits are exceeded, use a properly fitted NIOSH-approved respirator.

Other/General Protection

WASH THOROUGHLY AFTER HANDLING.

Ingredient(s) - Exposure Limits

AROMATIC HYDROCARBON BLEND

ACGIH TLV: NOT ESTABLISHED

OSHA PEL: NOT ESTABLISHED

IARC: NO

NTP: NO

PROPRIETARY BLEND OF ALIPHATIC & CYCLIC AMINES

ACGIH TLV: NOT ESTABLISHED

OSHA PEL: NOT ESTABLISHED

IARC: NO

NTP: NO

SILICA, QUARTZ

ACGIH TLV-TWA 0.1 mg/m³ (Notice of Intended Change)

ACGIH TLV-TWA 0.05 mg/m³ (Proposed)

OSHA PEL-TWA 30/%SiO₂+2 mg/m³

OSHA PEL-TWA 10/%SiO₂+2 mg/m³

OSHA PEL-TWA 250/%SiO+5 mppcf

9. Physical And Chemical Properties

Appearance

VISCOUS LIQUID (VARIOUS COLORS)

Odor

AMINE ODOR

Chemical Type: Mixture

Physical State: Liquid

Melting Point: N/AV °F

Boiling Point: N/AV °F

Specific Gravity: 1.70

Vapor Pressure: N/AV

Vapor Density: >AIR

Solubility: N/AV

Evaporation Rate: SLOWER THAN ETHER

MATERIAL SAFETY DATA SHEET

Sikagard 62 - Part B (ALL COLORS)

10. Stability And Reactivity

Stability: STABLE

Hazardous Polymerization: WILL NOT OCCUR

Conditions To Avoid (Stability)

NONE KNOWN

Incompatible Materials

STRONG OXIDIZING AGENTS, ACID AND EPOXY RESINS UNDER UNCONTROLLED CONDITIONS

Hazardous Decomposition Products

CO, CO₂, OXIDES OF NITROGEN

11. Toxicological Information

Miscellaneous Toxicological Information

Conditions Aggravated By Exposure

EYE DISEASE, SKIN DISORDERS AND ALLERGIES, CHRONIC RESPIRATORY CONDITIONS

Ingredient(s) - Carcinogenicity

SILICA, QUARTZ

NTP - Listed On The National Toxicology Program

Listed In The IARC Monographs

12. Ecological Information

No Data Available...

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

Proper Shipping Name

NOT REGULATED BY D.O.T.

15. Regulatory Information

U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

SARA Hazard Classes

Acute Health Hazard

Chronic Health Hazard

SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

State Regulations

WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects, or other reproductive harm.

MATERIAL SAFETY DATA SHEET

Sikagard 62 - Part B (ALL COLORS)

15. Regulatory Information - Continued

Ingredient(s) - State Regulations

BENZYL ALCOHOL

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

SILICA, QUARTZ

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

California - Proposition 65

Massachusetts - Hazardous Substance

16. Other Information

HMIS Rating

Health: 3

Fire: 1

Reactivity: 0

PPE: C

Revision/Preparer Information

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201-933-8800

This MSDS Supercedes A Previous MSDS Dated: 11/27/2001

Disclaimer

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikacorp.com or 201-933-8800.

SIKA CORPORATION

Printed Using MSDS Generator™ 2000