

Material Safety Data

May 2007

TRADE NAME: Sikanol -M

Page 1/2

1.1 Chemical

Liquid plasticizer agent, normal setting air entraining Integral mortar admixture.

1.2 Characterization:

Form: Liquid Color: Brown. Odor: Characteristic.

2. Physical Data and Safety Data

Density 20° C $\sim 1.00 \pm 0.005$ Kg/l **pH Value** (100 g/l H₂O) 7.5 (typical)

Hazardous decomposition products After evaporation of water, combustion

will generate: oxides of carbon. Polymer monomers, acrid smoke and irritating

fumes.

Hazardous Reactions Exothermic reaction.

3. Regulation.

A void contact with skin and eyes.

4. Protective measures storage and handling

4.1 Technical protective measures Storage temperature min/max. : +5 / +25° C

Keep only in the original container.

Keep container tightly closed.

Keep away from heat and frost.

Avoid dust formation during application.

Keep away from extremes of cold.

4.2 'Personal Protective Equipment

Respire.: Protection mask.

Eye Protection: Tightly fitting protective goggles

Hand Protection: Gloves. E.g. rubber, minimum thickness 1.4 mm

Others: N.A

4.3 Industrial Hygiene

During use. Eating, drinking or smoking is not allowed. Remove immediately

contaminated clothing. Wash hands before breaks and sfter work.

4.4 Protection Against Fire and Explosion

N.A.

4.5 Disposal

Arrange for disposal via a licensed waste contractor.

Dispose of containers with care.

Empty packaging should be removed by a licensed waste

contractor.

Dispose as special waste: mixture of water and hydrocarbons.

TRADE NAME: Sikanol -M

Page 2/2

6. **Measures in Case of Accidents and Fires** After spillage or leakage

Sweep up with sweeping aid and dispose as prescribed Remove residues with water.

Extinguish media: Water. Foam carbon dioxide, dry powder.

Not to be used : N.A.

First Aid:

In case of contact with eyes. Rinse immediately under running water for 15 minutes with eyelids open. Seek medical advice.

Take off immediately all contaminated clothing. Wash contaminated skin with plenty of soap and water.

If swallowed, drink copious amounts of water without delay and seek medical advice. Do not induce vomiting.

7. **Transport**

Non-Toxic under relevant health and safety codes.

Contact with eyes, skin and mucous membrane causes burns. Sensitization and allergic reactions may occur due to its cement base.

8. **Toxicology**

Non-Toxic under relevant health and safety codes.

9. **Ecology**

Don't dispose of into water or soil, but according to local regulations. In cured state the product is not known to cause an adverse environmental effect. Because of the effect of pH value the product can be injurious to aquatic life.

SIKA EGYPT

Cairo Sales Office El Obour City – 1st Industrial Zone

Block no. 13035/10

P.O. Box: 2943 El Horria (11361) Cairo

Phone: +2-02-46100715/8 Fax: +2-02-46100759





Alex. Sales Office

4, Mohamed Masoud St., Beh. Olemby

Club

P.O.Box 2579 El Sarai + Alexandria

Phone: 4244601 /2/3/5 Fax: 4244604 **Borg El Arab Factory**

Tel.: 4592654 - 4591417 Fax: 4592036