# **Safety Data Sheet**

July 2018

TRADE NAME: SIKADUR – 42MP Part (A)

Page 1/4

#### 1.1 Chemical

Modified polyamine

1.2 Characterization:

Form: Liquid Color: Clear Odor: Neutral.

2. Physical Data and Safety Data

 Flash Point
 150 °C

 Density
 20° C

 PH value
 20° C

 N/A

**Thermal decomposition** Non if correctly handled

**Hazardous decomposition products** No decomposition if used as prescribed.

**Hazardous Reactions** No hazardous reactions when stored and handling.

# 3. Safety Precautions

Accidental splashes to the skin must be washed off with soap and water.

Accidental splashes to the eyes or mucous membrane must be rinsed with clean warm water.

# 4. Protective measures storage and handling

# 4.1 Technical protective measures

Store free from frost and naked flame.

Store in cool, dry, well ventilated area.

Don't pour into drain.

Keep only in the original container.

Keep container tightly closed and dry.

#### 4.2 Personal Protective Equipment

**Respiratory protection**: Required if used confined areas or if ventilation is inadequate.

**Eye Protection :** Tightly fitting protective goggles

**Hand Protection:** Gloves. E.g. rubber, minimum thickness 1.4 mm **Others:** Experts always wear the right protective clothing

#### 4.3 Industrial Hygiene

During use. Eating, drinking or smoking is not allowed. Remove immediately contaminated clothing. Wash hands before breaks and after work.

#### 4.4 Protection Against Fire and Explosion

N.A.

#### 4.5 Disposal

Dispose as special waste: mixture of water and hydrocarbons.

N.A = not applicable

blank = no data available



TRADE NAME: SIKADUR - 42MP Part (A)

Page 2/4

#### 5. First Aid:

In case of contact with eyes. Rinse immediately under running water for 15 minutes with eyelids open. Seek medical advice.

Take off immediately all contaminated clothing. Wash contaminated skin with plenty of soap and water.

If swallowed, drink copious amounts of water without delay and seek medical advice. Do not induce vomiting.

# 6. Transport

Non-hazardous.

# 7. Toxicology

Non-toxic under relevant health and safety codes.

# 8. Ecology

Don't release into water supplies or the ground. In cured state the product is not known to cause an adverse environmental effect. Because of the high pH value the product can be injurious to aquatic life.

# 9. Stability and reactivity

Chemical stability

This material is thermally stable when stored and used as directed.

Conditions to avoid:

Evaluated temperatures.

Incompatible Materials:

No information available.

Hazardous decomposition products:

Oxides of carbon, smoke and other toxic fumes.

Hazardous reactions:

No information available.

# 10. Disposal considerations

Refer to State/Territory Land Waste Management Authority.



**TRADE NAME:** SIKADUR - 42MP Part (A) Page 3/4

# 11. Regulatory information

Poisons Schedule (Aust): Not applicable.

# 12. Handling and storage

#### **Handling:**

Avoid skin and eye contact.

#### **Storage:**

Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from incompatible materials described in section 9.

Keep containers closed when not in use – check regularly for leaks.

# 13. Exposure controls/personal protection

National occupational exposure limits:

No value assigned for this specific material

#### **Biological limit values:**

As per the "National Model Regulations for the control of Workplace Hazardous Substances [NOHSC: 1005 (1994)]" the ingredients in this material do not have a Biological Limit Allocated.

#### **Engineering measures:**

Provide exhaust ventilation where operating conditions may create excessive work place vapor or mists.

#### **Personal protection equipment:**

OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES.

Wear overalls, safety glasses and impervious gloves.

#### 14. Fire-fighting measures:

Specific hazards:

Non – combustible material.

Specific protective precautions and equipment:

Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapor or products of combustion.



TRADE NAME: SIKADUR - 42MP Part (A) Page 4/4

15.

# **Hazard identification**

Hazard Category: Risk Phrase(s) : Safety Phrase(s):

**16.** 

# Consumption/information on ingredients

Chemical characterization: **Modified polyamine** 

Hazardous ingredients:

SIKA EGYPT

Cairo Sales Office 222 El Hegaz St. , Heliopolis P.O. Box : 2943 El Horria (11361) Cairo Phone : +202 – 26235032 / 4

Fax: +202 - 26235637

Alex. Sales & Factory

4, Mohamed Masoud St. ,Beh. Olemby Club P.O.Box 2579 El Sarai + Alexandria

Phone: 4244601 /2/3/5 Fax: 4244604 **Borg El Arab Factory** 

Tel.: 4592654 - 4591417 Fax: 4592036