

PRODUCT DATA SHEET

Sika® Bitucoat®-M

RUBBER BITUMEN EMUSLION COATING

DESCRIPTION

Sika® Bitucoat®-M one component bitumenous emulsion containing rubber, for the protection and damp proofing of concrete surfaces subject to attack from mild soil acids and salts
Suitable for use in hot and tropical climatic conditions

USES

Sika® Bitucoat®-M is used to protect concrete surfaces that will subsequently be back filled such as:

- Retaining walls, Basements and Foundations.
- General waterproofing and damp proofing of concrete foundations that are in contact with groundwater.
- Adhesive for insulating boards.
- Separation coating for concreting work (bond-breaker).

FEATURES

- Low odour, dries without producing strong vapour.
- Excellent adhesion to many substrates.
- It can be used for damp surfaces.
- High resistance to chemical and salts.

CERTIFICATES AND TEST REPORTS

Sika® Bitucoat®-M complies with ASTM D1227 Type 3 Class 2
VOC content < 100 g/l

PRODUCT INFORMATION

Packaging	200 kg drums , 18&15 Kg Pails
Shelf life	12 months from date of production if stored properly in original unopened packing
Storage conditions	In dry conditions and under maximum temperature 45 °C. Away of frost and direct sunlight.
Colour	Brown black turns to black film after drying.
Density	1.05 ± 10% kg/litre

APPLICATION INFORMATION

Consumption	0.35 – 0.50 kg/m ² for 1 st coat 0.15 – 0.30 kg/m ² for 2 nd coat depending on substrate porosity
Curing time	max 7 days

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

MIXING

Add 5-10% of water to 1st coat.
Stir to achieve homogeneous consistency of the product.

APPLICATION

By brush, roller.
Stir thoroughly before use.
Minimum 2 coats are required.

CLEANING OF EQUIPMENT

Clean all tools and equipment immediately after use with soap and water, use Sika Thinner 2 to dissolve dried material.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

Sika Egypt

1st Industrial Zone (A)
Section #10, Block 13035
El Obour City, Egypt
TEL: +202 44810580
FAX: +202 44810459
egy.sika.com



Product Data Sheet

Sika® Bitucoat®-M

August 2024, Version 01.01
02072560100000009