

PROVISIONAL PRODUCT DATA SHEET 2021-12-21

SikaWall®-321 Putty

Pre- packed Acrylic base For Putty Application

DESCRIPTION

SikaWall®-321Putty is ready to use wall putty ,based on vinyl acrylate polymer emulsion ,especially selected fillers,binding materials and antibacterial agents

USES

SikaWall®-321 Putty is used as an economical and easy to apply leveling putty for internal applications for all concrete types.

CHARACTERISTICS / ADVANTAGES

SikaWall®-321Putty offers the following advantages:

- One component
- Ready to use
- Easy applying and finish
- smooth and ideal surface

SUSTAINABILITY

SCAQMD Rule 1113 Volatile Organic Compound (VOC)
= 12 g/l

PRODUCT INFORMATION

Packaging	20 Kg pails
Appearance and colour	White
Shelf life	12 months from date of production if stored properly in original unopened packing.
Storage conditions	Store in a dry cool place protected from heat and direct sunlight
Density	1.75 Kg/L
Solid content	75%

APPLICATION INFORMATION

Consumption	250-300 gm/ per coat depends on concrete surface roughness and the required thickness of the applied layer
Layer thickness	1-2mm

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

Ecology : Do not dispose into water or soil but according to local regulations

Transport: Non -hazardous

Safety Precautions: In contact with skin, wash off with soap and water. In contact with eyes or mucous mem-

brane, rinse immediately with clean warm water and seek medical attention without delay.

Toxicity : Non-toxic under relevant health and safety codes.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

The substrate must be sound, clean, dry, free from dust, oil, grease and laitance etc.

All traces of release agents must be removed. On chalky and dusty surfaces, all loose particles must be removed by stiff bristle brush.

APPLICATION

In Case of smooth surfaces, apply one coat of SikaWall®-321Putty using a normal putty knife.

Apply two or more coats in case of coarse surfaces. Each coat must be dried and sanded down before applying the next coat.

Drying times are generally related to air circulation, temperature, film thickness and number of coats, and will be affected correspondingly.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Egypt

1st Industrial Zone (A)
Section #10, Block 13035
El Obour City, Egypt
TEL: +202 44810580
FAX: +202 44810459
egy.sika.com



Provisional Product Data Sheet 2021-12-21

SikaWall®-321 Putty

March 2021, Version 01.02

021840103000000029