

METHOD STATEMENT

Sika Tile Grout®

DATE, : 07/2015

VERSION NO.01

SIKA EGYPT

ENG. ASHRAF ELZINY

TECHNICAL DEPARTMENT


Scope: *Sika Tile Grout*[®] is a single component powder, containing cement with selected hydraulic binders, organic binders, waterproofing materials and inert hard aggregates.

Suitable for grouting ceramic tiles and similar applications.

1. Mixing

- 1.1 The recommended homogenous, smooth paste consists of
1.0 – 1.20 liters water to 4.0 kg Powder.

in case of 25 kg add 6.25 – 7.5 litre of clean water



- 1.2 Mix well with a hand trowel.

- 1.3 For large volume mixing. A slow speed drill is recommended.

2. Application

- 2.2 Apply *Sika Tile Grout*[®] to the space between using a sponge or piece of soft cloth.

- 2.3 Work the paste into the joints and around edges.



2.4 Remove surplus grout from the face of the tile using dry cloth.

2.5 When the grout is completed, polish tiles with dry cloth.

For any further clarification don't hesitate to contact Sika Egypt Technical Department.

Technical Department

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Egypt
TECHNICAL DEPARTMENT

Version given by
Eng. Ashraf Elziny
Phone: 002-01223271730
Fax: 002-03-4244604
Mail: elziny.ashraf@eg.sika.com

Method Statement
Sika Tile Grout®
DATE, : 07/2015, VERSION NO.01