



TRADE NAME : *Sika BituSeal*

1.1 Chemical

Product Modified Bitumen Waterproofing Membrane consists of:

A Polymer modified Bituminous compound of softening point higher than 145°C (modifying polymer are Polypropylene).

1.2

Characterization :

Form: Synthetic reinforcement in the middle **Color:** Black internally

Odor: Negligible.

2. Physical Data and Safety Data

Flammability point

Not applicable.

Softening point

135 - 155°C (depending on type of compound)

Solubility in water

Insoluble

Incompatibility with:

Water, water solutions, acid & basic solutions, fertilizers and construction materials which are in contact with.

Resistant to:

Atmospheric agents and industrial environment.

3. Regulation.

Contact with skin is Safe.

4. Protective measures storage and handling

4.1 Personal Protective Equipment

Respire. : Protection mask.

Eye Protection : Tightly fitting protective goggles

Hand Protection: Gloves. E.g. rubber , minimum thickness 1.4 mm

Others : N.A

4.2 Industrial Hygiene

During use. Eating, drinking or smoking is not allowed. Wash hands before breaks and work.

4.3 Protection Against Fire and Explosion

Contains volatile solvent, do not heat.

Solvent based – for indoor use insure adequate ventilation.

4.4 Disposal

Arrange for disposal via a licensed waste contractor.

Dispose of containers with care.

TRADE NAME : *Sika BituSeal*Page 2/2

First Aid:

In case of contact with eyes. Rinse immediately under running water for 15 minutes with eyelids open. Seek medical advice.

7. Transport

Non- Hazardous under relevant health and safety codes.

8. Toxicology

Non-Toxic under relevant health and safety codes.

SIKA EGYPT**Cairo Sales Office**

El Obour City – 1st Industrial Zone

Block no. 13035/10

P.O. Box : 2943 El Horria (11361) Cairo

Phone : +2-02-46100715/ 8

Fax : +2-02-46100759

**Alex. Sales Office**

4, Mohamed Masoud St. ,Beh. Olemby Club

P.O.Box 2579 El Sarai + Alexandria

Phone : 4244601 /2/3/5

Fax : 4244604

Borg El Arab Factory

Tel. : 4592654 - 4591417 Fax: 4592036