



Material Safety Data

May 2007

TRADE NAME : **SIKA Plug**

Page 1/2

1.1 Chemical

Mixture of cement, additive and sand ready for use as a high strength repair mortar.

1.2 Characterization :

Form : powder

Color : gray

Odor : none

2. Physical Data and Safety Data

Density 20° C ~ 1.7 Kg/l

pH Value (100 g/l H₂O) 14

Thermal decomposition 550 Degrees Celsius

Hazardous decomposition products Cao

Hazardous Reactions Exothermic reaction with acids.

3. Regulation.

A void contact with skin and eyes.

4. Protective measures storage and handling

4.1 Technical protective measures Storage temperature min/max. : +5 / +40° C

Keep only in the original container.

Keep container tightly closed.

Keep away from heat and frost.

Avoid dust formation during application.

Keep away from acids.

4.2 Personal Protective Equipment

Respire. : Dust protection mask.

Eye Protection : Tightly fitting protective goggles

Hand Protection: Gloves. E.g. rubber , minimum thickness 1.4 mm

Others : N.A

4.3 Industrial Hygiene

During use. Eating, drinking or smoking is not allowed. Remove immediately contaminated clothing. Wash hands before breaks and after work.

4.4 Protection Against Fire and Explosion

N.A.

4.5 Disposal

Dispose as special waste: mixture of water and hydrocarbons.

5. Measures in Case of Accidents and Fires

5.1 After spillage or leakage

Sweep up with sweeping aid and dispose as prescribed

Remove residues with water.

5.2 Extinguish media: Water. Foam carbon dioxide, dry powder.

Not to be used : N.A.

5. First Aid:

- 3** In case of contact with eyes. Rinse immediately under running water for 15 minutes with eyelids open. Seek medical advice.
Take off immediately all contaminated clothing. Wash contaminated skin with plenty of soap and water.
If swallowed, drink copious amounts of water without delay and seek medical advice. Do not induce vomiting.

6. Transport

Non-Toxic under relevant health and safety codes.
Contact with eyes, skin and mucous membrane causes burns. Sensitization and allergic reactions may occur due to its cement base.

7. Toxicology

Non-Toxic under relevant health and safety codes.

8. Ecology

Don't dispose of into water or soil, but according to local regulations.
In cured state the product is not known to cause an adverse environmental effect.
Because of the high pH value the product can be injurious to aquatic life.

SIKA EGYPT

Cairo Sales Office

El Obour City – 1st Industrial Zone
Block no. 13035/10
P.O. Box : 2943 El Horria (11361) Cairo
Phone : +2-02-6100715/ 8
Fax : +2-02-6100759



Alex. Sales Office

4, Mohamed Masoud St. ,Beh. Olemby Club
P.O.Box 2579 El Sarai + Alexandria
Phone : 4244601 /2/3/5
Fax : 4244604

Borg El Arab Factory

Tel. : 4592654 - 4591417 Fax: 4592036