



# MATERIAL SAFETY DATA SHEET

## Sikadur® 330 US - Part A

### HMIS

HEALTH	2
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	C

### 1. Product And Company Identification

**Supplier**

Sika Corporation  
201 Polito Ave  
Lyndhurst, NJ 07071

Company Contact: EHS Department  
Telephone Number: 201-933-8800  
FAX Number: 201-933-9379  
Web Site: www.sikausa.com

**Manufacturer**

Sika Corporation  
201 Polito Ave  
Lyndhurst, NJ 07071

Company Contact: EHS Department  
Telephone Number: 201-933-8800  
FAX Number: 201-933-9379  
Web Site: www.sikausa.com

**Supplier Emergency Contacts & Phone Number**

CHEMTREC: 800-424-9300  
INTERNATIONAL: 703-527-3887

**Manufacturer Emergency Contacts & Phone Number**

CHEMTREC: 800-424-9300  
INTERNATIONAL: 703-527-3887

Issue Date: 08/17/2007

Product Name: Sikadur® 330 US - Part A  
CAS Number: Not Established  
Chemical Family: Filled and modified reactive resin  
MSDS Number: 4159  
Product Code: 033313N

### 2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
AROMATIC HYDROCARBON BLEND	Mixture	
EPOXY RESIN	25068-38-6	

### 3. Hazards Identification

**Eye Hazards**

Causes eye irritation.

**Skin Hazards**

May cause skin irritation. Prolonged and/or repeated skin contact may cause an allergic reaction/sensitization.

**Ingestion Hazards**

Harmful if swallowed.

**Inhalation Hazards**

May cause respiratory tract irritation.

# MATERIAL SAFETY DATA SHEET

## Sikadur® 330 US - Part A

### 4. First Aid Measures

#### Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

#### Skin

In case of contact, immediately flush skin with soap and plenty of tepid water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

#### Ingestion

Dilute with water. Do not induce vomiting. Never give anything by mouth to an unconscious victim. Contact physician.

#### Inhalation

Remove to fresh air. If breathing has stopped, institute artificial respiration. Consult a physician.

### 5. Fire Fighting Measures

**Flash Point:** >215 °F 102 °C

**Autoignition Point:** N/AV °F

#### Fire And Explosion Hazards

None known

#### Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

#### Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

### 6. Accidental Release Measures

Avoid release to the environment. Use appropriate Personal Protective Equipment (PPE). Contain spill and collect with absorbent material and transfer into suitable containers. Do not flush to sewer or allow to enter waterways. Ventilate enclosed area.

### 7. Handling And Storage

#### Handling And Storage Precautions

Keep out of reach of children. Store in a cool well ventilated area. Keep containers tightly closed.

#### Storage Precautions

Protect from frost. Protect from heat and direct sunlight.

#### Work/Hygienic Practices

Wash thoroughly with soap and water after handling product.

### 8. Exposure Controls/Personal Protection

#### Engineering Controls

Use with adequate general and local exhaust ventilation. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

#### Eye/Face Protection

Safety glasses with side shields or goggles.

#### Skin Protection

Avoid skin contact. Wear long sleeve shirt and long pants. Wear chemical resistant gloves.

# MATERIAL SAFETY DATA SHEET

## Sikadur® 330 US - Part A

### 8. Exposure Controls/Personal Protection - Continued

#### Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace conditions warrant a respirator's use.

#### Other/General Protection

Wash thoroughly with soap and water after handling.

### 9. Physical And Chemical Properties

#### Appearance

White paste

#### Odor

Mild aromatic odor

**Chemical Type:** Mixture

**Physical State:** Solid

**Melting Point:** N/AV °F

**Boiling Point:** N/AV °F

**Specific Gravity:** 1.37

**Packing Density:** N/AV

**Vapor Density:** > Air

**Solubility:** N/AV

### 10. Stability And Reactivity

**Stability:** Stable

**Hazardous Polymerization:** Will not occur

#### Conditions To Avoid (Stability)

None known

#### Incompatible Materials

Strong oxidizing materials, acids, bases.

#### Hazardous Decomposition Products

CO, CO<sub>2</sub>

#### Conditions To Avoid (Polymerization)

Hazardous reactions with Amines, Phenols

No decomposition if used as prescribed.

### 11. Toxicological Information

No Data Available...

### 12. Ecological Information

No Data Available...

### 13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

# MATERIAL SAFETY DATA SHEET

## Sikadur® 330 US - Part A

### 14. Transport Information

#### Proper Shipping Name

Not Regulated by the US DOT

### 15. Regulatory Information

#### U.S. Regulatory Information

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

#### SARA Hazard Classes

Acute Health Hazard  
Chronic Health Hazard

#### SARA Section 313 Notification

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

### 16. Other Information

#### HMIS Rating

Health: 2

Fire: 1

Reactivity: 0

PPE: C

#### Revision/Preparer Information

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201-933-8800

This MSDS Supercedes A Previous MSDS Dated: 01/19/2005

### Disclaimer

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikacorp.com](http://www.sikacorp.com) or 201-933-8800.

SIKA CORPORATION



# MATERIAL SAFETY DATA SHEET

## Sikadur® 330 US- Part B

### HMIS

HEALTH	*3
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	D

### 1. Product And Company Identification

**Supplier**

Sika Corporation  
201 Polito Ave  
Lyndhurst, NJ 07071

**Company Contact:** EHS Department  
**Telephone Number:** 201-933-8800  
**FAX Number:** 201-933-9379  
**Web Site:** www.sikausa.com

**Manufacturer**

Sika Corporation  
201 Polito Ave  
Lyndhurst, NJ 07071

**Company Contact:** EHS Department  
**Telephone Number:** 201-933-8800  
**FAX Number:** 201-933-9379  
**Web Site:** www.sikausa.com

**Supplier Emergency Contacts & Phone Number**

**CHEMTREC: 800-424-9300**  
**INTERNATIONAL: 703-527-3887**

**Manufacturer Emergency Contacts & Phone Number**

**CHEMTREC: 800-424-9300**  
**INTERNATIONAL: 703-527-3887**

**Issue Date:** 08/17/2007

**Product Name:** Sikadur® 330 US- Part B  
**CAS Number:** Not Established  
**Chemical Family:** Amines  
**MSDS Number:** 3441  
**Product Code:** 033314N

### 2. Composition/Information On Ingredients

Ingredient Name	CAS Number	Percent Of Total Weight
BLEND OF ALIPHATIC AMINES	Not Establis	

### 3. Hazards Identification

**Eye Hazards**

Corrosive to living tissue. Causes eye irritation. Causes eye burns.

**Skin Hazards**

Corrosive to living tissue. Contact with skin can cause irritation or burns. May cause skin sensitization.

**Ingestion Hazards**

Corrosive to living tissue. Harmful if swallowed.

**Inhalation Hazards**

Corrosive to living tissue. May cause burns.

# MATERIAL SAFETY DATA SHEET

## Sikadur® 330 US- Part B

### 4. First Aid Measures

#### Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

#### Skin

In case of contact, immediately flush skin with soap and plenty of water for at least 15 minutes. Get medical attention immediately if irritation (redness, rash, blistering) develops and persists.

#### Ingestion

Dilute with water. Do not induce vomiting. Never give anything by mouth to an unconscious victim. Contact physician.

#### Inhalation

Remove to fresh air. If breathing has stopped, institute artificial respiration. Consult a physician.

### 5. Fire Fighting Measures

**Flash Point:** >200 °F

**Autoignition Point:** N/AV °F

#### Fire And Explosion Hazards

Exposure to heat builds up pressure in closed containers.

#### Extinguishing Media

In case of fire, use water spray (fog) foam, dry chemical, or CO2.

#### Fire Fighting Instructions

In the event of a fire, firefighters should wear full protective clothing and NIOSH-approved self-contained breathing apparatus with a full facepiece operated in the pressure demand or other positive pressure mode.

### 6. Accidental Release Measures

Avoid release to the environment. Use appropriate Personal Protective Equipment (PPE). Contain spill and collect with absorbent material and transfer into suitable containers. Do not flush to sewer or allow to enter waterways. Ventilate enclosed area.

### 7. Handling And Storage

#### Handling And Storage Precautions

Keep out of reach of children. Store in a cool, dry, well ventilated area. Keep containers tightly closed.

#### Work/Hygienic Practices

Wash thoroughly with soap and water after handling.

### 8. Exposure Controls/Personal Protection

#### Engineering Controls

Use with adequate general and local exhaust ventilation. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

#### Eye/Face Protection

Faceshield over safety glasses or goggles.

#### Skin Protection

Avoid skin contact. Wear long sleeve shirt and long pants. Chemical resistant gloves.

#### Respiratory Protection

A respirator protection program that meets 29 CFR 1910.134 requirement must be followed whenever workplace

# MATERIAL SAFETY DATA SHEET

## Sikadur® 330 US- Part B

### 8. Exposure Controls/Personal Protection - Continued

#### Respiratory Protection - Continued

conditions warrant a respirator's use.

#### Other/General Protection

Wash thoroughly after handling.

### 9. Physical And Chemical Properties

#### Appearance

Gray paste

#### Odor

Amine odor

**Chemical Type:** Mixture

**Physical State:** Liquid

**Melting Point:** N/AV °F

**Boiling Point:** N/AV °F

**Specific Gravity:** 1.20

**Packing Density:** N/AV

**Vapor Density:** > Air

### 10. Stability And Reactivity

**Stability:** Stable

**Hazardous Polymerization:** Will not occur

#### Conditions To Avoid (Stability)

None Known

#### Incompatible Materials

Strong oxidizing agents, acid and epoxy resins under uncontrolled conditions.

#### Hazardous Decomposition Products

CO, CO<sub>2</sub>, Oxides of nitrogen, ammonia.

#### Conditions To Avoid (Polymerization)

None Known

### 11. Toxicological Information

#### Conditions Aggravated By Exposure

Eye disease, skin disorders and allergies, chronic respiratory conditions.

### 12. Ecological Information

No Data Available...

### 13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations. Waste generators must determine whether a discarded material is classified as a hazardous waste. USEPA guidelines for the classification determination are listed in 40 CFR Parts 261.3. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

### 14. Transport Information

No Data Available...

# MATERIAL SAFETY DATA SHEET

## Sikadur® 330 US- Part B

### 14. Transport Information - Continued

**Proper Shipping Name**

Corrosive Liquid, Basic, Organic, NOS (Aliphatic Amines)

**Hazard Class**

8 PGIII

**DOT Identification Number**

UN3267

**DOT Shipping Label**

Corrosive

### 15. Regulatory Information

**U.S. Regulatory Information**

All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

**SARA Hazard Classes**

Acute Health Hazard  
Chronic Health Hazard

**SARA Section 313 Notification**

This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372.

### 16. Other Information

**HMIS Rating**

Health: \*3

Fire: 1

Reactivity: 0

PPE: D

**Revision/Preparer Information**

MSDS Preparer: EHS Department

MSDS Preparer Phone Number: 201-933-8800

This MSDS Supersedes A Previous MSDS Dated: 01/19/2005

**Disclaimer**

The information contained in this Material Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Technical Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikacorp.com](http://www.sikacorp.com) or

# **MATERIAL SAFETY DATA SHEET**

## **Sikadur® 330 US- Part B**

<b>Disclaimer - Continued</b>
201-933-8800.
SIKA CORPORATION

Printed Using MSDS Generator™ 2000