

PRODUCT DATA SHEET

SikaMur[®]-113 Render Medium

High Quality, Cement Based, Finishing Coating and Decorative For Exterior & Interior Substrates

DESCRIPTION

Sika Mur[®]-113 Render Medium is one component cement based, ready to use as pre-packed for medium textured finishing render with high quality, color stable, decorative and extreme weather resistant.

USES

Sika Mur[®]-113 Render Medium is suitable for the following applications:

- Decorative applications over plastered and cementitious substrates.
- Improves concrete / masonry final appearance.
- Weathering Resistance for Exterior concrete surfaces.
- Economical medium textured final finish coat.

CHARACTERISTICS / ADVANTAGES

- One component, ready to use add only water.
- Easy to apply
- Very good adhesion to fair face concrete and cement surfaces.
- Gives final medium textured decorative surface.

APPROVALS / CERTIFICATES

Complies with EN 998 standard

PRODUCT INFORMATION

Packaging	25 Kg.
Appearance and colour	Color chart is available
Shelf life	12 months from date of production if stored properly in original unopened packing.
Storage conditions	Store in a dry cool place protected from heat and direct sunlight
Density	1.9 kg/l
Compressive strength	After 28 days: $\approx 5 \text{ N/mm}^2$ @23° C

APPLICATION INFORMATION

Mixing ratio	5.5 - 6.9 litre per 25 kg bag
Consumption	2.75 - 3.0 kg/m ² depends of concrete surface roughness and the thickness of the applied layer
Layer thickness	$\sim 2 - 3 \text{ mm}$.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY / PRE-TREATMENT

Substrates should be clean and free from any loose particles, dust, oil, grease, curing agents, or paint. Remove all loose materials mechanically, with a wire brush or sand blasting.

Pre-wet prior to the application of Sika Mur® - 113 Render Medium without leaving excess water (S.S.D)

MIXING

- Mixing using clean fresh water as per the required consistency.
- Mechanical mixing is recommended for the best application and performance.

APPLICATION

- While the substrate is still in a SSD condition, spread a layer of Sika Mur®-113 Render Medium by suitable hand tool immediately after mixing.
- For achieving the required texture use the suitable trowel while Sika Mur®-113 Render Medium is still wet.
- Sika Mur®-113 Render Medium can be applied with spraying machine.
- Plastered substrates should be left to cure sufficiently prior to application of Sika Mur®-113 Render Medium.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

Sika Egypt

1st Industrial Zone (A)
Section #10, Block 13035
El Obour City, Egypt
TEL: +202 44810580
FAX: +202 44810459
egy.sika.com



Product Data Sheet

SikaMur®-113 Render Medium
December 2021, Version 01.03
021810101000000017