

Method Statement for Application “SIKA EGYPT”

Sika Crack Seal®

Scope: 100% Acrylic elastomeric emulsion resin, mineral filler, geotextile fibres, surfactants and water, Paste form

(One component, adhesive and fine pore sealing and smoothing repair putty).

Preliminary Works and surface preparation

- 1.1 Clean out surfaces, using small wire brushes or compressed air to remove all loose and friable materials, as well as mud and other impurities.
- 1.2 All concrete surfaces must be clean, free from standing water and all loosely adhering particles.

2. Execution

o Mixing and Application

- 2.1 Sika Crack Seal is a ready to use product, no need for mixing or dilute.
- 2.2 Sika Crack Seal can be applied with trowel, putty knife, or similar tool. It can be applied with a sealant gun.

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Product Data Sheet for the product concerned, copies of which will be supplied on request



2.3 Apply directly to the prepared substrate into crack by trowel or putty knife.

2.3 Level smooth to surrounding surface.



Construction

***For any further clarification don't hesitate to contact Sika Egypt
Technical Department.***

**Sika Egypt
Technical Department**



Sika Egypt El Abour City 1st industrial zone (A) Section # 10 Block 13035,
Phone: +2 02 46100714 / Fax: +2 02 46100759
Mobil : 0123271730