

Sika Decap®

Concrete and Mortar Remover

Product Description Sika Decap® is a liquid containing blended acids, for removing concrete and mortars by chemical reaction to the lime of the cement

- Uses**
- Ceramic wall and floor tiles.
 - Cleaning of metal forms.
 - Ready mix vehicles.
 - Batching plants.
 - Various site tools.
 - Elimination of surface latents prior to coating applications.
 - Cleaning of exposed aggregates after the use of Rugasol Liquid or paste.

Technical Data

Type	Liquid
Density (at 20°C)	~ 1.4 kg/l
Packaging	5, 30 and 120 litre plastic containers.
Storage	Store in dry conditions.
Shelf life	18 months from date of production if stored properly in original unopened packing.

Application Details

- Application**
- Depending on thickness of material, Sika Decap® can be used in its pure form or diluted with water 1:2 max 1:3.
 - Applied by brush or spray.
 - A waiting time of 3 to 5 minutes to allow chemical reaction to take place.
 - Visual reaction is noted by a foaming action against the latents or mortars.
 - Mortars or latents are then removed by a metal spatular.
 - Large thicknesses of concrete are first removed by mechanical means.

Important Notes All areas that have been in contact with Sika Decap® must be washed down with clean water to remove residue of Sika Decap®.



Safety Instructions

Safety Precautions	Accidental splashes to the skin must be washed off with water and soap. Accidental splashes to the eyes or mucous membrane must be rinsed with clean warm water. Seek medical attention.
Ecology	Residues of material must be removed according to local regulations. Fully cured material can be disposed of as household waste under agreement with the responsible local authorities.
Transport	Hazardous
Toxicity	Non-Toxic under relevant health and safety codes.

Legal notes

The information, and in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.



Sika Egypt for Construction Chemicals
El Abour City
1st industrial zone (A)
Section # 10 Block 13035,
Egypt

Tel :+202- 44810580 - 90
Fax :+202- 44810459
Mob :+20122- 3908855
www.sika.com.eg

