

PRODUCT DATA SHEET

Sika® Bitumen-W

Bitumen Emulsion with High Viscosity

DESCRIPTION

A water base Bituminous coating for damp-proofing of concrete surfaces subjected to aggressive soils.

Sika Bitumen® -W is complies with ASTM D-1227 type 3 Class 2

USES

Sika Bitumen® -W is directly used for protection of foundations, basements and below ground concrete from salt attack.

It is used as a damp proof protective coating.

FEATURES

- Easy application (Brush, roller or airless spray).
- No heating required (cold application).
- Can be applied over damp surfaces.
- Increased coverage rates.
- Not contain solvent so no solvent odor and not need special health precaution during application
- High resistance to aggressive salts.

CERTIFICATES AND TEST REPORTS

Sika® Bitumen-W complies with ASTM D1227 type 3 class 2
VOC Content < 100 g/l.

PRODUCT INFORMATION

Composition	Bitumen Emulsion
Packaging	14 kg pails 200 kg drums
Shelf life	12 months from date of production if stored properly in original unopened packing.
Storage conditions	<ul style="list-style-type: none">▪ In dry conditions and under maximum temp. 40 °C.▪ Do not store in direct sunlight.▪ Avoid humidity, cold freezing conditions
Colour	Browne-black turns to black film after drying
Density	1.05 ± 10% kg/l

APPLICATION INFORMATION

Consumption	0.35 – 0.50 Kg/m ² , 1st coat. 0.15 – 0.30 Kg/m ² , 2nd coat, depending on substrate porosity.
Curing time	7 days
Waiting time to overcoating	Min. 2 hours (depending on ambient temperature)

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

All surfaces must be clean, free from oil, grease, standing water and all loosely adhering particles.

MIXING

Add 10-20 % of water to Sika Bitumen® -W to first coat and stir it to achieve homogeneous consistency of the product.

APPLICATION

By brush or roller.
Stir thoroughly before use.
Minimum 2 coats are required.

CLEANING OF EQUIPMENT

Clean with water for non-hardened material, for hardened materials use Sika Thinner 2.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.

Sika Egypt

1st Industrial Zone (A)
Section #10, Block 13035
El Obour City, Egypt
TEL: +202 44810580
FAX: +202 44810459
egy.sika.com



Product Data Sheet

Sika® Bitumen-W

August 2024, Version 02.01
02070630100000025