

PRODUCT DATA SHEET

SikaShield® W1 EG

CEMENTITIOUS ADHESIVE FOR WATERPROOFING MEMBRANES

DESCRIPTION

SikaShield® W1 EG is a 1-part polymer modified cementitious waterproofing adhesive for bonding the waterproofing membranes on concrete substrates.

USES

The Product is used for:

- Basements and other below ground structures.
- Horizontal reinforced concrete slabs, decks and podiums.
- Vertical reinforced concrete walls.

FEATURES

- Provides very good adhesion between the waterproofing membranes and the concrete surface.
- Fast and easy installation.
- Very good mechanical strength.
- Requires minimum surface preparation.
- Can be applied on wet concrete.
- A part of the waterproofing system acting as a second defence line after the membrane.

PRODUCT INFORMATION

Composition	Polymer modified cement
Packaging	25 kg bag
Shelf life	12 months from date of production.
Storage conditions	The Product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +35 °C. Always refer to packaging. Refer to the current Safety Data Sheet for information on safe handling and storage.
Appearance and colour	Powder/ White
Density	1.8 kg/l. (Fresh mortar)

APPLICATION INFORMATION

Consumption	~2.0–3.0 kg/m ² Note: Consumption data is theoretical and does not allow for any additional material due to surface porosity, surface profile, variation in level, wastage or any variations.
Mixing ratio	5-6 liters water to 25 kg powder
Pot Life	25 - 30 mins (at 25°C)

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

APPLICATION INSTRUCTIONS

SUBSTRATE QUALITY

When designing the waterproofing system, make sure that the supporting structure has sufficient structural strength to support all new and existing layers of the system build-up. New concrete substrates must be at least 3 days old. The substrate must be free of any sharp protrusion or burrs, clean, free of grease, laitance, oil and loosely adhering particles.

MIXING

Do not add more water than the prescribed amount to the powder. Excessive water addition can negatively affect the finished mechanical performance of the product.

1. Pour the minimum amount of water into a suitable clean mixing container.
2. While mixing, gradually add the powder.
3. Mix continuously for at least 2 minutes to achieve a uniform mix. If necessary, add more water up to the maximum amount to achieve the required consistency.
4. Leave the mixture to stand for 2 minutes.
5. Mix for an additional 1 minute.

APPLICATION

1. Saturate the substrate with clean water.
2. Pour the mixed SikaShield® W1 onto the substrate. Spread the SikaShield® W1 evenly using a 4-5 mm notched trowel.
3. Immediately apply the waterproofing membranes while the adhesive is still wet.
4. For further application advice, refer to the Product Data Sheets and Method Statement of the relevant waterproofing membranes.

Sika Egypt

1st Industrial Zone (A)
Section #10, Block 13035
El Obour City, Egypt
TEL: +202 44810580
FAX: +202 44810459
egy.sika.com



Product Data Sheet

SikaShield® W1 EG
April 2024, Version 03.01
02072560110000013

CLEANING OF EQUIPMENT

Clean all tools and application equipment with water immediately after use. Hardened material can only be removed mechanically

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request. It may be necessary to adapt the above disclaimer to specific local laws and regulations. Any changes to this disclaimer may only be implemented with permission of Sika® Corporate Legal in Baar.